

SATA® filter 414™/424™/434™/464™

SATA filter 414/424/434/464



Technical Data	
	Air inlet: G 1/2" female thread
	Air outlet: 1/4 " male thread
	Max. inlet operating pressure: 15.0 bar
	Max. outlet operating pressure: 10.0 bar
	Air flow at 6.0 bar: 3600 NI/min
	Max. ambient temperature: 120 °C
	Max. ambient temperature with activated charcoal: 60 °C

Pressure regulator/water separator

92288	SATA pressure reducer 420 with gauge 0-10 bar, air inlet and outlet G 1/2" (female thread)	
92213	SATA filter 414 single-stage sinter filter without pressure regulator, with outlet module (2 x 1/4" male thread)	
92254	SATA filter 414 L single-stage sinter filter without pressure regulator, for pipeline installation (G 1/2" female thread)	
92221	SATA filter 424 single-stage sinter filter, pressure regulator, outlet module (2 x 1/4" male thread)	
92262	SATA filter 424 L single-stage sinter filter, pressure regulator, for pipeline installation (G 1/2" female thread)	

Fine filter

92239	SATA filter 434 single-stage fine filter without pressure regulator, with outlet module (2 x 1/4" male thread)	
92270	SATA filter 434 L single-stage fine filter without pressure regulator for pipeline installation (G 1/2" female thread)	

Activated charcoal filter to retrofit SATA filter 444

141473	SATA filter 464 add-on kit single-stage activated charcoal filter without pressure regulator to retrofit SATA filter 444 to SATA filter 484	
92247	SATA filter 464 single-stage activated charcoal filter without pressure regulator, with outlet module (2 x 1/4" male thread)	

All prices are recommended list prices. Errors, technical modifications and printing errors reserved.

SATA® filter 444™/474™/484™



SATA filter 400

Technical Data	
	Air inlet: G 1/2" female thread
	Air outlet: 1/4" male thread
	Max. inlet operating pressure: 15.0 bar
	Max. outlet operating pressure: 10.0 bar
	Air flow at 6.0 bar: 3600 NI/min
	Max. ambient temperature: 120 °C
	Max. ambient temperature with activated charcoal: 60 °C

Combi filter		Euro
92296	SATA filter 444 double-stage sinter filter/fine filter with pressure regulator and outlet module (2 x 1/4" male thread)	
92833	SATA filter 444 with carrying support double-stage sinter filter/fine filter, pressure regulator, outlet module (2 x 1/4" male thread)	
92304	SATA filter 444 L double-stage sinter filter/fine filter with pressure regulator, for pipeline installation (G 1/2" female thread)	
92312	SATA filter 474 double-stage fine filter/activated charcoal without pressure regulator with outlet module (2 x 1/4" male thread)	
92320	SATA filter 484 triple-stage sinter filter/fine filter/activated charcoal with pressure regulator and outlet module (2 x 1/4" male thread)	
129619	SATA filter 484 with floor carrying support triple-stage sinter filter/fine filter/activated charcoal/floor carrying support with pressure regulator and outlet module (2 x 1/4" male thread)	
173195	SATA filter 484 mobil in a case, sintered filter/fine filter/activated charcoal with pressure regulator, air inlet G 1/2 a, air outlet (2x quick coupling)	

All prices are recommended list prices. Errors, technical modifications and printing errors reserved.