



SATAjet® X 5500 B RP®/HVL



- Revolutionary: The X-nozzles are taking atomization to a whole new level
- Noticeably quieter: Whispering nozzle™ due to optimized air flow geometry, reduced noise level in the relevant sound frequency ranges
- Individual: Matches any application requirement, such as specific characteristics of the paint system, climatic conditions and application method (application speed/application control)
- Precise: Optimized material distribution for enhanced spraying uniformity and atomization with both spray fan shapes
- Low maintenance: No air distribution insert required, thus also ensuring a much easier and faster cleaning process
- Consistent: Constant fan size across the entire nozzle spectrum (within each respective atomization technology) with linear increases of the material flow rate
- Efficient: The optimized atomization concept enables to realize considerable material savings using the same application method as before

SATAjet® X 5500 RP® STANDARD / DIGITAL

Technical Data




www.sata.com/SATAjetX5500

Inlet pressure
Field of application: 7 psi - 34 psi
Compliant: max. 29 psi

Air consumption at 29 psi: 10 cfm

Spray distance
Field of application: 3.9 inches - 8.2 inches
Recommended: 6.6 inches - 8.2 inches



Nozzle	I-nozzle					O-nozzle				
	1.1 l	1.2 l	1.3 l	1.4 l	-	1.1 0	1.2 0	1.3 0	1.4 0	-
Standard with RPS multi-purpose cup 0.6 l / 0.9 l (each 1x) with swivel joint										
Part No.	1061548	1061556	1061564	1061572	-	1061580	1061598	1061605	1061613	-
DIGITAL with RPS multi-purpose cup 0.6 l / 0.9 l (each 1x) with swivel joint										
Part No.	1061639	1061655	1061704	1061738	-	1061770	1061796	1061811	1061837	-
Nozzle	1.1 l	1.2 l	1.3 l	1.4 l	-	1.1 0	1.2 0	1.3 0	1.4 0	-
Nozzle set										
Part No.	1063536	1063544	1063552	1063560	-	1063578	1063586	1063594	1063601	-

SATAjet® X 5500 HVL STANDARD / DIGITAL

Technical Data




www.sata.com/SATAjetX5500

Inlet pressure
Field of application: 7 psi - 34 psi
HVL: max. 29 psi

Air consumption at 29 psi: 15 cfm

Spray distance
Field of application: 3.9 inches - 8.2 inches
Recommended: 3.9 inches - 5.9 inches



Nozzle	I-nozzle					O-nozzle				
	1.1 l	1.2 l	1.3 l	1.4 l	1.5 l	1.1 0	1.2 0	1.3 0	1.4 0	1.5 0
Standard with RPS multi-purpose cup 0.6 l / 0.9 l (each 1x) with swivel joint										
Part No.	1061895	1061902	1061887	1061910	1061928	1061936	1061944	1061952	1061960	1061978
DIGITAL with RPS multi-purpose cup 0.6 l / 0.9 l (each 1x) with swivel joint										
Part No.	1062009	1061986	1062017	1062041	1062059	1062083	1062091	1062132	1062140	1062174
Nozzle	1.1 l	1.2 l	1.3 l	1.4 l	1.5 l	1.1 0	1.2 0	1.3 0	1.4 0	1.5 0
Nozzle set										
Part No.	1063619	1063627	1063635	1063651	1063669	1063677	1063685	1063643	1063693	1063700